



# TAA-compliant Tripp Lite series SmartOnline UPS systems



## Enhanced performance and TAA compliance for government contracts

The refreshed Tripp Lite series SmartOnline® UPS family includes models that comply with the federal Trade Agreements Act (TAA). These TAA-compliant UPS systems are eligible for General Services Administration (GSA) Schedule contracts, making them an option for government and military agencies and contractors.

Network capability, long battery runtimes and an easy-to-use LCD control panel make these rack/tower double-conversion UPS models an outstanding value for minimizing downtime in network closets, server rooms and edge computing sites.

### Power and protect sensitive IT equipment

#### Highest level of power protection

Double-conversion technology continually converts incoming AC power into DC power, and then resynthesizes it back into AC power with a pure sine wave.

- Continuous on-line operation isolates sensitive equipment from power problems on the AC line.
- Automatic restart after outages reduces the need for onsite visits.
- In the event of an overload or internal UPS fault, the load is transferred to utility power to maintain operation (without battery backup).

#### Reliable battery backup to prevent downtime

Zero transfer time to battery allows uninterrupted operation.

- User-replaceable, hot-swappable VRLA internal batteries outlast brief outages and permit graceful system shutdown during longer blackouts.
- Battery runtime can be extended with up to four optional external battery packs (sold separately).

### Easily monitor and manage UPS operation

#### User-friendly local monitoring and control

Status LEDs and a menu-driven LCD make it easier to identify alarms and faults. The control panel rotates to accommodate horizontal or vertical UPS installation.

#### Advanced remote monitoring

The 6000 VA UPS includes a TAA-compliant network card (WEBCARDLXE) for SNMP-based remote management. The network card is sold separately for the 1500, 2000 and 3000 VA models. Free downloadable PowerAlert software supports remote monitoring and control.

- USB and RS-232 serial ports provide additional communication options. (Cables are included.)
- RPO and ROO functions allow remote shutdown or restart of connected equipment.
- Optional TAA-compliant environmental monitoring sensors are available: E2MT, E2MTDO and E2MTHDI. (Network card is required.)




Mount the UPS in a rack or use the included tower stands for vertical placement.



Powering Business Worldwide


**Feature focus** (See [TrippLite.Eaton.com](http://TrippLite.Eaton.com) for model-specific configurations.)

Model: SU1500RTXLCD2UTAA



- 1 Status indicators (online, battery, bypass, fault)
- 2 Menu-driven LCD
- 3 Control buttons (escape, up, down, enter, on/off)
- 4 Rack-mounting brackets (removable)
- 5 Input power cord with plug
- 6 Network card slot (WEBCARDLXE sold separately)
- 7 RPO/ROO connector
- 8 USB communication port
- 9 RS-232 (DB9) serial communication port
- 10 Relay output connector

Model: SU6000RT3UTAA



- 11 External battery pack detection port
- 12 External battery pack connector
- 13 Ground screw
- 14 Primary group outlets
- 15 Group 1 programmable outlets
- 16 Group 2 programmable outlets
- 17 Remote power off (RPO) connector
- 18 Network management card (included)
- 19 Remote on/off (ROO) connector
- 20 Circuit breakers (200–240V 20A)
- 21 (2) L6-20R outlets
- 22 (2) L6-30R outlets
- 23 Input and output terminal blocks

**Specifications**

Catalog number	Rating (VA/watts)	Internal runtime*, Full/half load	Plus 1 external battery pack*, Full/half load	External battery pack compatibility	Output connections	Input connection	Dimensions (H x W x D)	Net weight
<b>120V 2U rack/tower UPS with network card slot</b>								
SU1500RTXLCD2UTAA	1500/1350	5.8/16.5 min.	27/63 min.	BP48RT2UTAA	(8) 5-15R	5-15P w/8 ft. cord	3.4 x 17.3 x 17.7 in.	42.6 lb.
SU2200RTXLCD2UTAA	2000/1800	7.7/20.2 min.	33.1/76 min.	BP72RT2UTAA	(1) L5-20R, (6) 5-20R	5-20P w/8 ft. cord	3.4 x 17.3 x 23.8 in.	61.5 lb.
SU3000RTXLCD2UTAA	3000/2700	4.8/13.9 min.	23/53.1 min.	BP72RT2UTAA	(1) L5-30R, (6) 5-20R	L5-30P w/8 ft. cord	3.4 x 17.3 x 23.8 in.	63 lb.

**208V 3U rack/tower UPS with WEBCARDLXE network card**

SU6000RT3UTAA	6000/5400**	3/8 min.	16/38 min.	BP180RT3UTAA	(2) L6-20R, (2) L6-30R, Hardwire	L6-30P w/10 ft. cord or Hardwire	5.1 x 17.3 x 27 in.	106 lb.
---------------	-------------	----------	------------	--------------	----------------------------------	----------------------------------	---------------------	---------

Due to continuous improvement programs, all specifications are subject to change without notice. SmartOnline UPS has a two-year limited warranty and \$250,000 Ultimate Lifetime Insurance. \*Runtime varies with load, battery age and other factors. UPS accepts up to four external battery packs. \*\*5400W at 230/240V, derated to 4800W at 208V.

**External battery packs**

Catalog number	Description
BP48RT2UTAA	48V 2U rack/tower external battery pack, TAA
BP72RT2UTAA	72V 2U rack/tower external battery pack, TAA
BP180RT3UTAA	180V 3U rack/tower external battery pack, TAA

Eaton  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
Eaton.com

© 2024 Eaton  
All Rights Reserved  
Printed in USA  
BR153201EN / 24-07-031  
September 2024

To learn more, contact your Eaton sales representative.



Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

